SAFETY DATA SHEET

Revision Date 18-Jun-2015 Version 1

1. IDENTIFICATION

Product identifier

Product Name All Purpose Aluminum

Other means of identification

 Product Code
 37470

 UN/ID no.
 UN1950

 SKU(s)
 None

Recommended use of the chemical and restrictions on use
Recommended Use
Uses advised against
No information available

Details of the supplier of the safety data sheet

Manufacturer Address Van Sickle Paint Mfg. Co. PO Box 82222 Lincoln, NE 68501

Phone: 402-476-6558 Fax: 402-476-6749

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Skin corrosion/irritation | Category 2 |
|--|-------------|
| Serious eye damage/eye irritation | Category 2A |
| Skin sensitization | Category 1 |
| Germ cell mutagenicity | Category 1B |
| Reproductive toxicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 1 |
| Aspiration toxicity | Category 1 |
| Flammable aerosols | Category 1 |

Emergency Overview

Danger

Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause genetic defects

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol



Appearance No information available

Physical state Aerosol

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- May be harmful if swallowed
- · Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

Unknown acute toxicity

24.11% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Weight-% | Trade Secret |
|-----------------------------------|------------|----------|--------------|
| Toluene | 108-88-3 | 15 - 40 | * |
| Solvent Naphtha, Medium Aliphatic | 64742-88-7 | 15 - 40 | * |
| Linseed Oil, polymerized | 67746-08-1 | 10 - 30 | * |
| Aluminum Powder | 7429-90-5 | 1 - 5 | * |
| Stoddard Solvent | 8052-41-3 | 1 - 5 | * |
| n-Butanol | 71-36-3 | 1 - 5 | * |
| Methyl Ethyl Ketoxime | 96-29-7 | 0.1 - 1 | * |

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Immediate medical attention is required. In case of accident or unwellness, seek medical

advice immediately (show directions for use or safety data sheet if possible). If symptoms

persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact Wash off immediately with plenty of water. Wash contaminated clothing before reuse. If skin

irritation persists, call a physician. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and

shoes.

Inhalation Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer

artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Immediate medical attention is not required. Move to fresh air in case of

accidental inhalation of vapors. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Rinse mouth. If symptoms persist, call a physician. Clean mouth

with water and drink afterwards plenty of water. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

WARNING: Spontaneous combustion (fire) may result from materials such as rags, steel wool, paper, clothing, and other waste soaked in linseed oil. Place in a sealed, water filled, metal container to prevent this.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Use personal protective equipment as required.

Keep people away from and upwind of spill/leak.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent

material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert

absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other

sharp object into opening on top of can.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep

containers tightly closed in a cool, well-ventilated place.

Incompatible materials Strong oxidizing agents. Strong acids. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-------------------------------|----------------------------------|---|---|
| Toluene 108-88-3 | TWA: 20 ppm | TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m³ Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m³ STEL: 150 ppm STEL: 560 mg/m³ |
| Aluminum Powder 7429-90-5 | TWA: 1 mg/m³ respirable fraction | TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 15 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction (vacated) TWA: 5 mg/m³ Al Aluminum | TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust TWA: 5 mg/m³ Al |
| Stoddard Solvent 8052-41-3 | TWA: 100 ppm | TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³ | IDLH: 20000 mg/m³ Ceiling: 1800 mg/m³ 15 min TWA: 350 mg/m³ |
| n-Butanol 71-36-3 | TWA: 20 ppm | TWA: 100 ppm TWA: 300 mg/m³ (vacated) S* (vacated) Ceiling: 50 ppm (vacated) Ceiling: 150 mg/m³ | IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m³ |

NIOSH IDLH Immediately Dangerous to Life or Health

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 Other Information

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.

Skin and body protection No special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Aerosol

No information available No information available Odor **Appearance** No information available Odor threshold No information available Color

Property Values Remarks • Method

pН No information available Melting point/freezing point No information available >= -42 °C / 230 °F Boiling point / boiling range -104 °C / -156 °F Flash point **Evaporation rate** No information available Flammability (solid, gas) No information available

Flammability Limit in Air Upper flammability limit:

No information available No information available Lower flammability limit: Vapor pressure No information available Vapor density No information available

Specific Gravity 0.87

Water solubility No information available Solubility in other solvents No information available **Partition coefficient** No information available No information available Autoignition temperature **Decomposition temperature** No information available Kinematic viscosity No information available No information available Dynamic viscosity **Explosive properties** No information available No information available **Oxidizing properties**

Other Information

No information available Softening point Molecular weight No information available **VOC Content (%)** No information available

Density 6.15 lbs/gal

No information available **Bulk density**

37470 All Purpose Aluminum

| Percent solids by weight | 26.3% |
|----------------------------|-------|
| Percent volatile by weight | 73.7% |
| Percent solids by volume | 21.9% |
| Actual VOC (lbs/gal) | 5.4 |
| Actual VOC (grams/liter) | 642.8 |
| EPA VOC (lbs/gal) | 5.4 |
| EPA VOC (grams/liter) | 642.8 |
| EPA VOC (lb/gal solids) | 24.5 |

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Strong acids. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation No data available.

Eye contact No data available.

Skin Contact No data available.

Ingestion No data available.

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|---|--|-----------------------|
| Toluene 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |
| Solvent Naphtha, Medium Aliphatic 64742-88-7 | > 5000 mg/kg (Rat) | = 3000 mg/kg (Rabbit) | > 5.28 mg/L (Rat) 4 h |
| n-Butanol 71-36-3 | = 700 mg/kg (Rat) = 790 mg/kg (Rat) | = 3400 mg/kg (Rabbit) = 3402 mg/kg (Rabbit) | > 8000 ppm (Rat) 4 h |
| Methyl Ethyl Ketoxime 96-29-7 | = 930 mg/kg(Rat) | = 0.2 mg/kg(Rabbit) | = 20 mg/L (Rat) 4 h |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---------------|-------|------|-----|------|
|---------------|-------|------|-----|------|

| Toluene | - | Group 3 | - | - |
|----------|---|---------|---|---|
| 108-88-3 | | · | | |

IARC (International Agency for Research on Cancer) Group 3 - Not classifiable as a human carcinogen

Reproductive toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.

STOT - single exposureSTOT - repeated exposure
No information available.
No information available.

Chronic toxicity Contains a known or suspected reproductive toxin. Avoid repeated exposure. May cause

adverse liver effects.

Target Organ Effects Central nervous system, Eyes, kidney, liver, Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

Ecotoxicity

Harmful to aquatic life with long lasting effects

28.22% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|-----------------------------------|----------------------------------|--|---------------------------------|
| Toluene | 433: 96 h Pseudokirchneriella | 15.22 - 19.05: 96 h Pimephales | 5.46 - 9.83: 48 h Daphnia magna |
| 108-88-3 | subcapitata mg/L EC50 12.5: 72 h | promelas mg/L LC50 flow-through | mg/L EC50 Static 11.5: 48 h |
| | Pseudokirchneriella subcapitata | 12.6: 96 h Pimephales promelas | Daphnia magna mg/L EC50 |
| | mg/L EC50 static | mg/L LC50 static 5.89 - 7.81: 96 h | |
| | | Oncorhynchus mykiss mg/L LC50 | |
| | | flow-through 14.1 - 17.16: 96 h | |
| | | Oncorhynchus mykiss mg/L LC50 | |
| | | static 5.8: 96 h Oncorhynchus | |
| | | mykiss mg/L LC50 semi-static 11.0 - | |
| | | 15.0: 96 h Lepomis macrochirus | |
| | | mg/L LC50 static 54: 96 h Oryzias | |
| | | latipes mg/L LC50 static 28.2: 96 h | |
| | | Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h | |
| | | | |
| | | Poecilia reticulata mg/L LC50 static | |
| Solvent Naphtha, Medium Aliphatic | 450: 96 h Pseudokirchneriella | 800: 96 h Pimephales promelas | 100: 48 h Daphnia magna mg/L |
| 64742-88-7 | subcapitata mg/L EC50 | mg/L LC50 static | EC50 |
| n-Butanol | 500: 96 h Desmodesmus | 1730 - 1910: 96 h Pimephales | 1983: 48 h Daphnia magna mg/L |
| 71-36-3 | | promelas mg/L LC50 static 1740: 96 | EC50 1897 - 2072: 48 h Daphnia |
| | Desmodesmus subspicatus mg/L | h Pimephales promelas mg/L LC50 | magna mg/L EC50 Static |
| | EC50 | flow-through 100000 - 500000: 96 h | |
| | | Lepomis macrochirus µg/L LC50 | |
| | | static 1910000: 96 h Pimephales | |
| | | promelas µg/L LC50 static | |
| Methyl Ethyl Ketoxime | 83: 72 h Desmodesmus subspicatus | | 750: 48 h Daphnia magna mg/L |
| 96-29-7 | mg/L EC50 | promelas mg/L LC50 flow-through | EC50 |
| | | 760: 96 h Poecilia reticulata mg/L | |
| | | LC50 static 320 - 1000: 96 h | |
| | | Leuciscus idus mg/L LC50 static | |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

| Chemical Name | Partition coefficient |
|---------------|-----------------------|
| Toluene | 2.65 |
| 108-88-3 | |

37470 All Purpose Aluminum

| n-Butanol 71-36-3 | 0.785 |
|----------------------------------|-------|
| Methyl Ethyl Ketoxime 96-29-7 | 0.65 |

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U031 U220 U239

| Chemical Name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---------------|------|----------------------------|------------------------|------------------------|
| Toluene | U220 | Included in waste streams: | - | U220 |
| 108-88-3 | | F005, F024, F025, F039, | | |
| | | K015, K036, K037, K149, | | |
| | | K151 | | |
| n-Butanol | - | Included in waste stream: | - | U031 |
| 71-36-3 | | F039 | | |

| Chemical Name | RCRA - Halogenated Organic Compounds | RCRA - P Series Wastes | RCRA - F Series Wastes | RCRA - K Series Wastes |
|---------------------|---|------------------------|--|------------------------|
| Toluene 108-88-3 | - | - | Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution. | . |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status | |
|------------------------------|-----------------------------------|--|
| Toluene 108-88-3 | Toxic Ignitable | |
| Aluminum Powder 7429-90-5 | Ignitable powder | |
| n-Butanol 71-36-3 | Toxic | |

14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1950
Proper shipping name Aerosols
Hazard Class 2.1

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to DOT.

Description UN1950, Aerosols, 2.1

Emergency Response Guide 126

Number

TDG

UN/ID no. UN1950 Proper shipping name Aerosols Hazard Class 2.1

UN1950, Aerosols, 2.1 Description

MEX

UN/ID no. UN1950 Proper shipping name Aerosols

Hazard Class

Description UN1950, Aerosols, 2

ICAO (air)

UN/ID no. UN1950 Proper shipping name Aerosols **Hazard Class** 2.1 **Special Provisions** A145, A167

Description UN1950, Aerosols, 2.1

IATA

UN/ID no. UN1950

Proper shipping name Aerosols, flammable

Hazard Class 2.1 **ERG Code** 10L

Special Provisions A145, A167, A802

UN1950, Aerosols, flammable, 2.1 Description

IMDG

UN/ID no. UN1950 Proper shipping name Aerosols **Hazard Class** F-D, S-U EmS-No.

Special Provisions 63,190, 277, 327, 344, 959 Description UN1950, Aerosols, 2

RID

UN/ID no. UN1950 Proper shipping name Aerosols **Hazard Class** 2.1 Classification code 5F

UN1950, Aerosols, 2.1 Description

ADR

UN/ID no. UN1950 Proper shipping name Aerosols Hazard Class 2.1 Classification code 5F **Tunnel restriction code** (D)

190, 327, 344, 625 **Special Provisions** Description UN1950, Aerosols, 2.1, (D)

Labels 2.1

ADN

Proper shipping name Aerosols **Hazard Class** 2.1 Classification code 5F

Special Provisions 190, 327, 344, 625 Description UN1950, Aerosols, 2.1

Hazard label(s) 2.1

Limited quantity (LQ) 1 L

Ventilation VE01, VE04

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies * Does not comply * **EINECS/ELINCS ENCS** Does not comply * **IECSC** Complies * Complies * **KECL PICCS** Does not comply * Does not comply * **AICS**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % | |
|-----------------------------|-------------------------------|--|
| Toluene - 108-88-3 | 1.0 | |
| Aluminum Powder - 7429-90-5 | 1.0 | |
| n-Butanol - 71-36-3 | 1.0 | |

SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardYesFire hazardYesSudden release of pressure hazardNoReactive HazardNo

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Toluene 108-88-3 | 1000 lb | X | X | Х |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|----------------------|--------------------------|----------------|---|
| Toluene 108-88-3 | 1000 lb 1 lb | - | RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ |
| n-Butanol 71-36-3 | 5000 lb | - | RQ 5000 lb final RQ RQ 2270 kg final RQ |

^{*} This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 | |
|--------------------------|---------------------------|--|
| Toluene - 108-88-3 | Developmental | |
| | Female Reproductive | |
| Ethyl Benzene - 100-41-4 | Carcinogen | |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|--|------------|---------------|--------------|
| Toluene 108-88-3 | Х | X | X |
| Solvent Naphtha, Medium Aliphatic 64742-88-7 | X | - | - |
| Aluminum Powder 7429-90-5 | X | X | X |
| Stoddard Solvent 8052-41-3 | Х | X | X |
| n-Butanol 71-36-3 | Х | X | X |
| Xylene 1330-20-7 | Х | X | X |
| Cobalt neodecanoate 27253-31-2 | Х | - | X |
| Neo C9-13 Acid, Cobalt Salts 68955-83-9 | Х | - | X |
| 1,2,4-Trimethylbenzene 95-63-6 | Х | X | X |
| Diethylene Glycol Methyl Ether 111-77-3 | Х | X | X |
| Propylene Glycol Methyl Ether 107-98-2 | Х | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

| Chemical Name | Weight % of HAPS in Product | Pounds HAPS / Gal Product |
|---------------|-----------------------------|---------------------------|
| Toluene | 36.85% | 2.68 |
| 108-88-3 | | |

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 Physical and Chemical Properties
HMIS Health hazards 2 Flammability 3 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Revision Date 18-Jun-2015 Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet