

1532

Barn and Outbuilding Latex Flat White Finish



Product Data Sheet

PRODUCT DESCRIPTION:

Tallman Ag Specialty Barn and Outbuilding is our quality latex coating, custom-designed for use on farm and ranch buildings, other utility buildings and fences. It is specifically formulated to provide high hiding, excellent color and outstanding exterior durability. Tallman's Barn Paint is extremely resistant to cracking, chipping, peeling and blistering.

TYPICAL USES:

Tallman Ag Specialty Barn and Outbuilding can be used on all sound properly prepared surfaces of wood, siding, trim, masonry, concrete block, asbestos shingles and properly primed metal.

BASES & COLORS:

Flat White Latex

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	1532
GENERAL TYPE:	Exterior Latex Flat
COLOR:	White
GLOSS:	1-10 @ 60°
SOLIDS BY WEIGHT:	43.7%
SOLIDS BY VOLUME:	23.3%
THEORETICAL COVERAGE @ 1 MIL DFT:	438 SF./Gal
RECOMMENDED DFT:	2.0 – 2.5 mils DFT
VISCOSITY @ 78°F:	95-100 KU
WEIGHT PER GALLON:	10.8-10.9 lbs.
FLASH POINT:	None
VOC:	62.8 G/L

SURFACE PREPARATION:

Proper surface preparation is the most important variable in determining the service life of a coating. For best results, all surfaces must be clean, dry and free from wax, oil, grease, dirt, mildew, loose rust, and any other contaminants. **NEW WOOD SURFACES:** prime with at least one coat of exterior primer. **PREVIOUSLY PAINTED WOOD SURFACES:** remove all loose cracking and peeling paint, surface chalk, dust and dirt. Glossy surfaces should be lightly sanded. Prime bare spots with appropriate primer. After surface has been properly prepared, apply two coats of Exterior Latex Barn Paint. **MASONRY:** must cure at least 60 days and be clean, free of dirt and sand. Old masonry must be thoroughly cleaned of peeling paint, loose sand, efflorescence and mildew. Chalky surfaces must be cleaned and pre-dampened just before paint application. Apply two coats of Tallman's Exterior Latex. **METAL:** prime bare metal with Tallman Equipment Enamel Primer. Two coats of primer are recommended allowing ample time to dry. Topcoat with one or two coats of Tallman's Latex Barn Paint.

APPLICATION:

Apply by nylon or polyester brush, roller or AIRLESS spray. Do not thin except for airless spray application, in which case you may thin with up to 10% clean water, if needed. May be applied to slightly damp surfaces. Do not mix with solvent paints, oils, thinners or turpentine. Before and during application, stir the paint thoroughly from the bottom of the can with an upward motion, scraping the bottom to avoid pigment settling.

ENVIRONMENTAL VARIABLES:

Apply only when surface and air temperatures are between 50° and 90°F. Avoid painting late in the day when dew and condensation are likely to form or when rain is threatening. Avoid painting on hot days in direct sunlight. Cool, wet, humid or over-applied coatings can greatly decrease a thorough cure and interfere with proper film formation. Always allow applied coat to dry before applying subsequent coats.

Dry-Times:

Drying time for this product will be approximately 1 hour to touch and may be recoated after 6 hours under ideal drying conditions.

1532

**Barn and Outbuilding Latex
Flat White Finish**



Product Data Sheet

CLEAN-UP:

Clean up all tools and equipment with warm, soapy water before paint is allowed to dry.

CAUTIONS:

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Tallman's does not control the application of its products, or the condition of the surfaces to which they are applied, Tallman Ag Specialty's® liability will under no circumstances exceed replacement of the product.